No. 634 Type ‘P’ Casing Scraper

The **Type P Casing Scraper** is used to remove scale, cement sheath, perforating burs, and other foreign matter from the casing walls. This provides a clean surface for running and setting subsurface equipment.

The casing scraper is designed with a one piece body, and has a full 360° cleaning coverage of the casing I.D. The blades provide a large by-pass area between the scraper blades. Each blade is secured into an individual pocket in the body to provide blade support against thrust and rotational loads. All blade loads are transferred through the body, not through the retaining system.



Features

The **Type P Casing Scraper** may be run on tubing or drill pipe and operates equally well when reciprocated vertically or rotated. Rotation is the preferred system in areas where the sub surface equipment is to be set.

Large sizes are available on request.

* Optional connection EUE pin up of same nominal size, EUE Pin is available in place of the API Reg. Pin Up. Applies to top connection only.

No. 634 Casing Scraper Specifications

Size	Casing Weight	Number	Blade Diameter	
			Collapsed	Extended
in	lbs/ft		in	in
mm	kg/m		mm	mm
4 1/2	6.75 – 21.60	634-450	3.72	4.44
114.3	10.04 – 32.14		94.49	112.73
5	8.00 – 21.40	634-500	4.10	4.81
127.0	11.90 – 31.84		104.24	122.17
5 1/2	9.00 – 26.80	634-550	4.38	5.43
139.7	13.39 – 39.88		118.18	137.95
5 3/4	14.00 – 25.20	634-575	4.47	5.61
146.1	20.83 – 37.49		113.72	142.54
6 5/8	12.00 - 26.60	634-650	5.35	6.43
168.2	17.86 – 39.87		135.76	163.32
7	13.00 – 35.00	634-700	5.70	6.95
177.8	19.34 – 52.07		144.77	176.58
7 5/8	20.00 – 39.00	634-750	6.38	7.47
193.7	29.76 – 58.03		161.93	189.64
8 5/8	20.00 – 49.00	634-850	7.35	8.49
219.1	29.76 – 72.91		186.63	215.67
9 5/8	29.30 – 58.40	634-950	8.31	9.42
244.5	43.59 – 86.88		211.14	239.17
10 3/4	32.75 – 81.00	634-10750	9.02	10.50
273.1	48.73 – 120.51		229.11	266.70
13 3/8	48.00 – 102.00	634-13375	12.01	13.11
339.7	71.41 – 151.76		305.05	338.08